

CERTIFICATE OF COMPLIANCE

Certificate Number 20140129-E365227
Report Reference E365227-20140128
Issue Date 2014-JANUARY-29

Issued to: MOORE INDUSTRIES - INTERNATIONAL INC
16650 SCHOENBORN ST
SEPULVEDA CA 91343-6106

**This is to certify that
representative samples of**

POWER CIRCUIT AND MOTOR-MOUNTED APPARATUS
FOR USE IN HAZARDOUS LOCATIONS

Refer addendum page for models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:


Standard No. ANSI/ISA 12.12.01, Nonincendive Electrical
Equipment for Use in Class I and II, Division 2 and Class III,
Divisions 1 and 2 Hazardous (Classified) Locations
Standard No. CAN/CSA C22.2 No. 213-M1987, Non-
incendive Electrical Equipment for Use in Class I, Division 2
Hazardous Locations

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and

"US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140129-E365227
Report Reference E365227-20140128
Issue Date 2014-JANUARY-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL - Series ECT Signal Isolators for use in Hazardous Locations, Class I, Div. 2 Groups A, B, C and D. Model ECT followed by either 4-20mA, 10-50mA, 1-5V, 0-10V, 0-150AC, 0-250AC, or 0-5AAC; followed by either 4-20mA, 10-50mA, 1-5V, 0-10V, 2x4-20mA, or 2x0-10V; followed by either 12-42DC, 24-42DC, 117AC, 230AC, 24DC, 4.5VLP, 5.5VLP, or 8.5VLP; followed by either EM, TX or RO; followed by [DIN].

USL, CNL - Series SCX Signal Isolators for use in Hazardous Locations, Class I, Div. 2 Groups A, B, C and D. Model SCX followed by either 4-20mA, 10-50mA, 1-5V, 0-10V, 0-150AC, 0-250AC, or 0-5AAC; followed by either 4-20mA, 10-50mA, 1-5V, 0-10V, 2x4-20mA, or 2x0-10V; followed by either 12-42DC, 24-42DC, 117AC, 230AC, 24DC, 4.5VLP, 5.5VLP, or 8.5VLP; followed by either EM, TX or RO; followed by [DIN]



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

