

CERTIFICATE OF COMPLIANCE

Certificate Number 20190727-E159337
Report Reference E159337-20190718
Issue Date 2019-JULY-27

Issued to: MOORE INDUSTRIES - INTERNATIONAL INC
16650 SCHOENBORN ST
NORTH HILLS CA 91343

This certificate confirms that representative samples of POWER CIRCUIT AND MOTOR-MOUNTED APPARATUS
See Addendum.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 508 and CSA C22.2 NO. 14-18, Industrial Control Equipment.

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number 20190727-E159337
Report Reference E159337-20190718
Issue Date 2019-JULY-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Signal Isolators – Models ECT followed by /, may be followed by -, followed by up to two digits, followed by -, followed by up to two digits, followed by mA or V, followed by /4-20mA, followed by /12-42DC, may be followed by /-RF or VTD, followed by [DIN] or FLB2.

Signal Isolators – Models SIX followed by followed by /, may be followed by -, followed by up to two digits, followed by -, followed by up to three digits, followed by mA or V, followed by /4-20mA or /10-50mA, followed by /12-42DC, may be followed by /-RF, -VTD, or -BI, followed by [DIN].



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

