

EPRX & RLX

Low-Cost, Linearizing RTD Transmitters

October 1993 Data Sheet 3 40

Description


Compact and economical, these loop-powered linearizing RTD transmitters accept input from 2- and 3-wire platinum RTD's. They convert the temperature input to a 4-20mA signal perfect for interface with an indicator, recorder or another process instrument. Linearization of the RTD signal ensures a highly accurate output (up to $\pm 0.1\%$ of span) that is linear to the input temperature.

Complete Temperature Assemblies—Moore Industries offers a complete line of temperature assemblies for use with the EPRX and the RLX including sensors, thermowells, and fittings. Accessories can be ordered separately, or as ready-to-install temperature assemblies. For information, refer to our Temperature Systems data sheet (#3.99).


Ordering Specifications

To order, use the bold face data from the Ordering Specifications section of the Specifications table. For assistance, refer to the model number example located at the bottom of the table.

Figure 1. Outline Dimensions and Terminal Designations



NOTE: Terminal designations shown are for the EPRX, which has three input terminals (A. B and C) to accept a 2- or 3-wire RTD. The RLX has two input terminals (A and B) to accommodate 2-wire RTD's only



Compact hockey-puck housings fit in wide variety of protective connection heads for mounting in almost any rugged field environment.

Features

- Highly accurate. Multi-point linearization ensures exceptional accuracy of ±0.1% of span.
- Mount in standard connection heads. Compact housings install quickly and securely in standard connection heads.
- Safe for hazardous locations. Intrinsic safety approvals and explosion-proof/flameproof connection heads provide protection in hazardous areas.
- Easy access adjustments. Span and zero adjustments are conveniently located on the front panel to make calibration quick and simple.

Certifications (see applicable options and enclosures)



Ex

BASEEFA (CENELEC) Intrinsically Safe EEx ia IIC T4

BASEEFA (CENELEC) Type N Ex NII T6 (RLX only)

CENELEC Flameproof, EEx d IIc T6

SAA Intrinsically Safe Ex ia IIC T4 (RLX only)

EPRX&RLX

Low-Cost, Linearizing RTD Transmitters

Specifications

Performance Accuracy: ±0.1% of span (includes the combined effects of linearity, hysteresis and repeatability)

Power Supply Effect: Negligable within specified

Burnout Protection:

Upscale to 28mA, standard (see -DD option for downscale drive)

Output Current Limiting: 150% of span typical

Performance Load Capability: (continued)

(Vs - 8.5V)/0.2A = ohms(see -LV option for EPRX)

Temperature

Ambient Operation: -40°C to +82°C (-40°F to +180°F) Effect on Amplifier:

EPRX: ±0.01% of span/°C maximum for spans greater than 15°C ±0.005% of span/°C typ. RLX: ±0.01% of span/°C typical; ±0.02% of span/ °C maximum

Adjustments Type: External multiturn

potentiometers Zero and Span: EPRX:

Indicator LED indicates ladequate

±10%; RLX: ±5%

power supplied for operation

Weight EPRX: 74 grams

(2.6 ounces) RLX: 62 grams (2.2 ounces)

Ordering Specifications

EPRX
(2- or 3-
wire RTD
input)
RLX
(2-wire
RTD input
only)

Unit

(Specify RTD or potentiometer type and temperature range)

RTD Type:

PT1 100 ohm platinum RTD PT5 500 ohm platinum RTD PT10 1000 ohm platinum RTD (alpha = .00385 ohms/ohm/°C)

Potentiometer Type (EPRX only): POT2W Current excited (rheostat). Full scale range may be between 10 ohms and 1 K

POT3W Voltage excited potentiometer input, any pot with 1K ohm and 50K ohm end resistance may be used Specify range in percent of electrical rotation

Standard Temperature Input Ranges:

0-50C 0 to +50°C 0-75C 0 to +75°C

0-100C 0 to +100°C

0-120C 0 to +120°C

0-150C 0 to +150°C 0-180C 0 to 180°C

0-200C 0 to +200°C 0-300C 0 to +300°C

0-400C 0 to +400°C

0-125F 0 to 125°F

0-200F 0 to 200°F 0-250F 0 to 250°F

0-300F 0 to 300°F 0-400F 0 to 400°F

Custom Input Ranges: To order a °C or °F range (within the limits of the available RTD types), specify the range next to the RTD type in the model number.

4-20MA Characterized to compensate for RTD nonlinearities

Output

EPRX: 8.5-42DC (up to 55V without damage) 8.5-28DC (required with -ISE option) 6.5-40DC (-LV

Power

BIX: 12-42DC 12-28DC (required with -ISE option)

required)

-ISE BASEFFA approved intrinsically safe (8.5-28DC power required for EPRX:

Options

12-28DC power required for RLX) -DD Downscale

drive to 3.5mA -DT Differential temperature input (EPRX only with two 2-wire

RTD's: no linearization with this option) -LV Low voltage

(EPRX only; no LEDY -N Type N

approval for Zone II areas (RLX only: requires F2LS housing)

-RO Reverse

meter input)

output (EPRX only; not available with -DT option or 3-wire potentioHousing

HPP Hockey-puck

housing CCP Clip for mounting in CH7 enclosure CPP Clip for mounting in 2HG and 2LS enclosures 2HG* HPP in 2-hub. high glass window, explosion-proof

enclosure 2LS* HPP in 2-hub. solid cover, explosion-proof enclosure CH4 HPP in cast iron connection head

CH5 Hockey-puck in cast aluminum connection head CH6 Hockey-puck

housing in plastic connection head CH7 Hockey-puck housing in explosionproof connection

*When F prefix is added to the model number, unit is CENELEC approved (e.g., F2LS)

head

When P suffix is added to the model number, the unit comes equipped with a base plate and U-bolts for mounting on a 2-inch pipe (e.g., 2LSP).

To order, specify: Unit / Input / Output / Power / Options [Housing]

Model number example: EPRX / PT1-0-100°C / 4-20MA / 8.5-42DC / -DD [HPP]



United States Tel: (818) 894-7111 FAX: (818) 891-2816

Australia Tel: (02) 525-9177 FAX: (02) 525-7296

The Interface Solution Experts

Belgium Tel: 03/235.35.44 FAX: 03/271.00.17

Netherlands Tel: (0)344-617971 FAX: (0)344-615920

United Kingdom Tel: 01293 514488 FAX: 01293 536852